


C1

Product Image		Features	
		★ F2.0 large aperture, more light inputs, clearer night vision	
		★ WiFi connection, remote access anytime and anywhere	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	VStarcam Ultra
2	Collection	Processor	Hi608
		Memory	512Mb
		Lens	3.6mm
		Image sensor	1/3.3" GC20C3 1080p Progressive Scan CMOS Sensor
		Min. Illumination	0.5Lux (Color), 0.1Lux (B/W)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Infrared night vision
		Field of View	79 ° diagonal
3	Video	Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP (Interpolated)
		Night vision	5-10 m
		Compression standard	H.265 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
4	Audio	Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency / Bit depth	8KHz/16bit
		Compression standard/Bit rate	G711A
5	PTZ	Movement range	N/A
6	Network	Network interface	N/A
		Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G-5.8G
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK
7	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Cloud storage supported (subscription required)
8	Alarm	Alarm detection	Motion detection, human detection, human framing, area detection
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 1.75W(0.35A), Max. Power : 3.25W (0.65A)
		Operating condition	Temperature: -10 ~ 45°C; Humidity: < 90%
		Weight	Net weight: 69g Gross weight: 198g
		Product Dimension	54x54x95mm
		Package Dimension	117x79x61mm
		Carton Dimension	485x415x330mm
		QTY/CTN	100PCS
Package Contents	Camera ×1, Magnetic mount ×1, Power adapter ×1, Power cable ×1, User manual ×1		