| FC4                   |                              |   |
|-----------------------|------------------------------|---|
| Product Image         |                              | Features  |
|                       |                              | ★ Dual lens ensuring coverage with no blind spots, two cameras in one                             |
|                       |                              | ★ High-brightness lighting, can be used for lighting and surveilance                              |
|                       |                              |   |
|                       |                              | ★F2.0 large aperture, more light intake, clearer night vision                                     |
|                       |                              | ★ISP image processing technology, preserving true colors  |
|                       |                              | ★ Human detection, real time alerts   |
| No. Sorts             | Туре                         | Parameters  |
| 1 System              | Operating system             | Linux   |
|                       | Online visitor               | Supports 4 visitors at the same time  |
|                       | APP                          | O-KAM Pro   |
| 2 Collection          | CPU                          | Ingenic   |
|                       | Memory                       | 512Mb   |
|                       | Lens                         | 4mm   |
|                       | Image sensor                 | 1/3" 1080p progressive scan CMOS sensor   |
|                       | Min. Illumination            | 0.5Lux (color mode), 0.1Lux (b&w mode)  |
|                       | Sensor performance           | Support automatic white balance, automatic gain control and automatic backlight compensation      |
|                       | Night vision                 | Black and white night vision, full-color night vision   |
|                       | Light brightness             | 1333φ   |
|                       | Viewing angle                | 88°   |
| 3 Video               | Resolution                   | 1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP  |
|                       | Night vision                 | 20-30meters   |
|                       | Compression standard         | H.264 main profile/Motion-JPEG/JPEG   |
|                       | IR control                   | IR-CUT, soft photosensitive control   |
|                       | Bit rate                     | 128 ~ 4096kbps  |
|                       | Image adjustment             | Brightness, contrast, OSD display   |
| 4 Audio               | Input                        | Built-in -38dB microphone   |
|                       | Output                       | Built-in 8Ω1W speaker   |
|                       | Sampling frequency/bit width | 8KHz/16bit  |
|                       | Compression standard/Bit     | G711A   |
| 5 Pan/Tilt            | Rotation angle               | Pan: 240° Tilt: 90°   |
| 6 Network             | Network interface            | 10Mbps/100Mbps; Adaptive/RJ45   |
|                       | Network protocol             | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P   |
|                       | Wireless network             | IEEE802.11b/g/n   |
|                       | Wireless frequency           | 2.4G  |
|                       | Wireless security encryption | 64/128-bit WEP/WPA-PSK/WPA2-PSK   |
| 7 Storage             | External TF card             | Supports T-Flash cards (up to 256GB)  |
|                       | Cloud storage                | Support cloud storage (sold separately)   |
| 8 Alarm               | Alarm detection              | Motion detection, human detection, human framing, human tracking, and area detection, siren alarm |
| 9 Physical Indicators | Rated voltage                | DC12V±5%  |
|                       | Power consumption            | Power: 6.24W (0.52A) Maximum power: 14.52W (1.21A)  |
|                       | Operating condition          | Working temperature: -10 ~ 55°C, working humidity <90%  |
|                       | Weight                       | Net weight: 812g, gross weight: 1350g   |
|                       | Camera size                  | 315x90x140mm  |
|                       | Packaging box size           | 337x120x170mm   |
|                       | Carton size                  | 525x350x510mm, 12PCS/Carton   |
|                       |                              |   |