AG623SR			
Product Image			Product Features
			★Supports AOV recording, 1 frame per second, long battery life
			★ Ultra-wide angle, six-motor gimbal control, flexible rotation, 360-degree unobstructed view.
			★Color night vision + black & white night vision. With the fill lights for enchaned lighting, it provides clearer images
			in low light conditions.
			★AI model algorithms, intelligent tracking, human feature analysis and targeting
			★Customize siren voice, audio and visual alarm
			★Free cloud storage
			★Three cloud storage ★Three lenses recording to guard different directions
			★ Dual light source, full color day and night
No.	Sorts	Туре	Parameters
1	System	Operating system	Linux
		Online visitor APP	Supports 4 visitors at the same time VStarcam Ultra
2	Collection	CPU	Hi3516CRNCV608
		Internal storage	1Gbit
		Image sensor	3*GC20C31/3.3
		Minimum illumination	0.8Lux/F1.4(color mode), 0.3Lux/F1.4(B&W mode)
			Fixed lens: focal length 4mm, 1G3P
		Lens	Pan&tilt lens: focal length 4mm, 1G3P
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Pan-Tilt	Adjust the angle of the tracking camera via App, pan 270 °, tilt 90 °;
			Manually adjust the angle of the panorama camera, pan 244 °, tilt 90 °.
		Viewing angle	D100°
3	Video	Night vision	Full color night vision, dual light source
		Compression standard	H.265 /MJPEF/JPEG
		Multi stream	Main stream: 1920*1080@15fps Sub stream: 640*384p@15fps
		IR control	When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function is disabled, IR is off and ICR is fixed in the day vision mode.
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps
		Image adjustment	Vertical, horizontal adjustable, OSD display
4	Audio	Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit Rate	G711A
5	•	Human detection	Human detection, filtering invalid video contents
		Area detection	Free daub, only monitoring the areas concerned by users
		Smart notification sound	Different devices push different sounds, so that you can know exactly which device is triggered
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios
		More AI functions (testing)	Pets, vehicles, parcels, etc
6 7 8	Key/interface	Network connection	Use APP to scan the QR code on device to add; Use the device to scan QR code on APP to add
		Cat1 China	FDD:B1/B3/B5/B8
			TDD:834/B38/B39/B40/B41
		Cat4 Overseas	European version/Japanese version/US version/Australian version
		Key 1	On/Off key
		Reset key External TF card	Long press to restore factory settings
			Support TF card (up to 256GB)
		Cloud storage	Support Sound and light alarm
		Sound light alarm Alarm detection	Sound and light alarm Support human detection
10	Physical Indicators	Rated voltage	DC5V/2.5A±5%
		Power supply	12000mAh battery powered
		Consumption	AOV mode 60mAh, working: 400MA-1.8A max
			Temperature: -10 ~ 55°C; Humidity: < 90%
			Net weight: 1220g Gross weight: TBD
		Weight Camera Size	192x286x173mm
		Packing list	Camera*1,TYPE-C*1, user manual*1, solar panel*2, solar panel bracket*2
—	I	i ackilig list	Camera 1,1112 C 1, user manuar 1, sorar paner 2, sorar paner Diduket 2