

AG621DR				
Product Image		Product Features		
No.	Sorts	Type	Parameters	
1	System	Operating system	Linux	
		Online visitor	Supports 4 visitors at the same time	
		APP	O-KAM Pro	
2	Collection	CPU	Hi3516CRNCV608	
		Internal storage	512MB	
		Image sensor	2*GC20C3 1/3.3	
		Minimum illumination	0.8Lux/F1.4(color mode), 0.3Lux/F1.4(B&W mode)	
		Lens	Fixed lens: focal length 4mm, 1G3P Pan&tilt lens: focal length 4mm, 1G3P	
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation	
3	Video	Pan-Tilt	Adjust the angle of the tracking camera via App, pan 270 °, tilt 90 °; Manually adjust the angle of the panorama camera, pan 180 °, tilt 90 °.	
		Viewing angle	D100°	
		Night vision	Full color night vision, dual light source	
		Compression standard	MJPEF/JPEG	
4	Audio	Multi stream	Main stream: 1920*1080@15fps Sub stream: 640*384p@15fps	
		IR control	When the IR night vision function is enabled, IR and ICR are automatically detected; when the IR night vision function is disabled, IR is off and ICR is fixed in the day vision mode.	
		Bit rate	CBR/VBR two rate control modes, and the output rate range is 128~4096kbps	
		Image adjustment	Vertical, horizontal adjustable, OSD display	
5	AI	Input	Built-in-38dB microphone	
		Output	Built-in 8Ω1W speaker	
		Sampling frequency/bit width	8KHz/16bit	
		Compression standard/Bit Rate	G711A	
		Human detection	Human detection, filtering invalid video contents	
6	Network	Area detection	Free dab, only monitoring the areas concerned by users	
		Smart notification sound	Different devices push different sounds, so that you can know exactly which device is triggered	
		Intelligent alarm sound	Set different equipment alarm sounds according to different scenarios	
		More AI functions (testing)	Pets, vehicles, parcels, etc	
7	Key/interface	Network connection	Use APP to scan the QR code on device to add; Use the device to scan QR code on APP to add	
		Cat1 China	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41	
		Cat4 Overseas	European/Japanese/American version	
8	Storage	Key 1	On/Off key	
		Reset key	Long press to restore factory settings	
9	Alarm	External TF card	Support TF card (up to 256GB)	
		Cloud storage	Free cloud storage	
10	Physical Indicators	Sound light alarm	Sound and light alarm	
		Alarm detection	Support human detection	
		Rated voltage	DC5V±5%	
		Power supply	10400mAh battery powered	
		Consumption	AOV mode: 50mAh, working: 400MA-1.8A max	
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%	
		Weight	Net weight: 680g; Gross weight: TBD	
Camera Size		183*164*122mm		
Packing list		Camera*1, user manual*1, solar panel*1, solar panel bracket*1		