

| CB54Q | | | |
|---|---------------------|---|---|
| Product Picture | | Features | |
|  | | <ul style="list-style-type: none"> ★Wireless connection ★Remote active wake-up, two-way voice intercom ★Quick start, start recording within 400ms ★Intelligent detection of human movement, intelligent alarm push ★5000mAh battery power supply, low power warning ★Ultra low power system optimization ★Support cloud storage to save alarm videos ★Support external 3W/5W solar panels, continuously transmit power, and the equipment won't not powered off | |
| No. | Category | Type | Parameter |
| 1 | System | Operating system | Embedded Linux |
| | | Online visitor | Supports 4 visitors at the same time |
| | | APP | O-KAM (Overseas Version) , O-KAM (Domestic Version) |
| 2 | Collection | Processor | T31ZX |
| | | Memory | 8M |
| | | Image sensor | GC4653, 500W |
| | | Minimum illumination | 0.8Lux/F1.4 ((Color mode)) ,0.3Lux/F1.4 (B&W mode) |
| | | Lens | Standard lens 4mm, 1G3P, IR-CUT integrated |
| 3 | Video | Sensor performance | Support Automatic white balance, Automatic gain control, Automatic backlight compensation |
| | | Viewing angle | D110° Diagonal |
| | | Night vision | Black and white night vision, Automatic switching of IR-CUT, 6 pcs 850nm IR LED lights, Night vision irradiation distance: 5 ~ 10m |
| | | Compression standard | H.265 /H.264 /MJPEF/JPEG |
| | | Multi-stream | 2592P/15fps (2592×1944) |
| 4 | Audio | IR control | IR night vision enables; IR, ICR automatic detection; IR OFF night vision function disabled/ IR always OFF, ICR is fixed in the day vision mode |
| | | Bit rate | CBR / VBR two rate control modes, and the output rate range is 128 ~ 4096kbps |
| | | Image adjustment | Brightness, contrast, vertical, horizontal adjustable, OSD display |
| | | Input | Built-in – 38dB microphone |
| | | Output | Built-in 8Ω1W speaker |
| 5 | Network | Sampling frequency/bit width | 8KHz/16bit |
| | | Compression standard / Bit | G711A |
| | | Network protocol | TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,P2P, IPV4 etc. |
| | | Wireless network | IEEE802.11b/g/n |
| | | Wireless frequency | 2.4~2.4835GHz |
| 6 | Key | Wireless security encryption | 64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption |
| | | Wireless connection | AP hotspot network configuration, QR code network configuration |
| | | Key1 | ON/OFF |
| | | Reset key | Long Press to restore the factory settings |
| | | 7 | Storage |
| 8 | Alarm | Storage capacity | Support T-Flash card (max 256GB) |
| | | Alarm detection | Support PIR human detection; Detection distance: 6m |
| | | Rated voltage | DC5V±5% |
| | | Power supply | Comes with 5000mAh battery power supply, 2*18650, supports external 3V, 5V solar panels |
| | | Power consumption | Sleep current 500uA, Working current: 390mA |
| 9 | Physical Indicators | Operating condition | Temperature: -10 ~ 50°C; Humidity: < 90% |
| | | Weight | Net weight: 192.5g; Gross weight: 597.5g |
| | | Product Dimensions | Camera size: 89.5*56.5*59.5mm; Color box size: 135x102x79mm |
| | | Packing list | Camera*1, Bracket*1, MICRO USB*1, Manual*1, (Solar power panel*1, Solar panel bracket*1 Optional) |