

CS2-SP			
Product Image		Features	
		<ul style="list-style-type: none"> ★ Dual lens dual view leaves no blind spots ★ F2.0 large aperture, more light inputs, clearer night vision ★ Dual core light board, supporting day and night full-color mode ★ ISP image processing technology, preserving true colors ★ Wireless connection (2.4-5.8GHz) ★ Human detection, real time alerts 	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	VStarcam Ultra
2	Collection	CPU	Ingenic T23N
		Memory	512Mb
		Lens	2.8mm
		Image sensor	1/2.7" 1080p progressive scanning CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight
3	Video	Night vision	Black and white night vision, full-color night vision
		Viewing angle	Diagonal: 100 °
		Resolution	1080P 1920x1080/15FPS/2MP; 1296P 2304x1296/15FPS/3MP (Interpolation)
		Night vision	5-10 meters
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
4	Audio	IR control	IR-CUT, soft photosensitive control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
		Input	Built-in -38dB microphone
5	Pan&Tilt	Output	Built-in 8Ω1W speaker
		Sampling	8KHz/16bit
		Compression	G711A
		Angle	Horizontal: 350 ° Vertical: 90 °
		Network interface	/
6	Network	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G-5.8GHz
		Wireless security	64/128-bit WEP/WPA-PSK/WPA2-PSK data encryption
		TF card	TF card (up to 256GB)
7	Storage	Cloud storage	Supports cloud storage functionality, available for purchase based on needs.
		Alarm detection	Motion detection, human detection, human framing, area detection, human tracking
9	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Power: 2.1W (0.42A) Maximum power: 3.25W (0.65A)
		Operating condition	Working temperature: -10~45 °C, working humidity<90%
		Weight	270g
		Camera size	116x114x114mm
		Packaging box size	124x120x178mm
		Carton size	620x515x380mm, 40PCS/CTN