


## AG623ZS

Product Image		Product Features	
		★ Features AOV mode, 24/7 recording at 1 frame per second.	
		★ Boasts an ultra-wide-angle lens and PTZ (Pan-Tilt-Zoom) capabilities, offering flexible rotation	
		★ Employs dual night vision modes (color and B&W), supported by supplemental lighting to ensure clear images in low-light conditions.	
		★ Leverages AI algorithms for intelligent tracking, featuring human detection and targeted	
		★ Offers customizable siren sounds and audio-visual alarms.	
		★ Support cloud storage	
		★ Four lenses to monitor different directions simultaneously.	
		★ Dual light source, full color day and night	
No	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	VStarcam Ultra
2	Collection	Processor	Hi3516CRNCV608
		Memory	1Gbit
		Image sensor	4*CV2005 1/3.0
		Min. Illumination	Color: 0.8 Lux @ (F1.6) B/W: 0.3 Lux @ (F1.6)
		Lens	Bullet channel: Focal length 4mm, 1G3P PTZ channel: Focal length 4mm (1G3P) + 12mm (1G2P)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		PTZ	PTZ channel (App Control): pan 270 °, tilt 90 °; Bullet channel (Manual adjustment): pan 244 °, tilt 90 °.
Field of View	100 ° diagonal		
3	Video	Night vision	Full-color night vision, dual-light source. PTZ channel: 4 dual-color dual-light LEDs Left bullet channel: 4 dual-color dual-light LEDs Right bullet channel: 4 dual-color dual-light LEDs
		Compression standard	H.265 /MJPEF/JPEG
		Multi stream	UHD:1920*1080@10fps; SD: 640*360p@10fps
		IR control	When IR night vision is enabled, the IR and ICR operate automatically; when disabled, IR stays off and ICR is fixed in day mode
		Bit rate	CBR/VBR control modes; Output range: 128~4096kbps
4	Audio	Image adjustment	Vertical, horizontal adjustable, OSD support
		Input	Built-in-38dB microphone
		Output	Built-in 8Ω1W speaker
		Sampling frequency/bit width	8KHz/16bit
5	AI	Compression standard/Bit	G711A
		Human detection	Detects human and filters out false alarms.
		Zone detection	Customizable monitoring zones; focus only on areas of interest.
		Smart notification sounds	Differentiated push notification sounds to identify which device was triggered.
		Smart alarm sounds	Set different device alarm sounds according to different scenarios.
6	Network	Advanced AI (testing)	Pet, vehicle, and package detection (under development).
		Network connection	Scan device QR code to add; Device scans APP QR code; Bluetooth configuration.
		Cat1 China	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41
7	Buttons	Cat4 Overseas	European version/Japanese version/US version/Australian version
		Power button	Power On/Off
8	Storage	Reset button	Long press to restore factory settings
		External TF card	Support TF card (up to 256GB)
9	Alarm	Cloud storage	Support
		Sound light alarm	Sound and light alarm
10	Physical Indicators	Alarm detection	Support human detection
		Rated voltage	DC5V/2.5A±5%
		Power supply	1600mAh battery powered
		Powe consumption	AOV mode 70mAh, operating range: 400MA-1.8A max.
		Operating condition	Temperature: -10 ~ 55°C; Humidity: < 90%
		Weight	Net weight: 1250g Gross weight: 2600g
		Camera Size	192x286x173mm
		Packing list	Camera*1, Type-C*1, user manual*1, solar panel*2 (including brackets)