

CG623ZS

Product image			Features
			★ Triple-channel real-time recording; dual-lens PTZ camera with 10x digital zoom
			★ Ultra-wide-angle surveillance, six-motor PTZ control enables flexible 360° rotation with no blind spots.
			★ Premium full-color + B&W night vision, dual-light LED fill light ensures clearer full-color imaging and brighter night vision.
			★ ISP image processing technology, preserves authentic colors and enhances image quality.
			★ Customizable alarm sounds, synchronized light and sound alerts for versatile application scenarios.
			★ AI human tracking, automatically follows and records human movement.
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Simultaneous Live View	Up to 4 users
		APP	VStarcam Ultra
2	Collection	SoC	Hi608
		Memory	512Mb
		Lens	PTZ camera: 3.6mm+12mm, left bullet channel: 3.6mm (1G3P) + right bullet channel: 3.6mm (1G3P)
		Image sensor	1/3.3" 1080p GC20C3 progressive scan CMOS sensor
		Min. Illumination	0.5 Lux (Color), 0.1 Lux (B/W)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Full-Color Night Vision, IR Night Vision
		Field of View	70°
3	Video	Resolution	Main stream: 1080P/1920x1080/10FPS, Substream: 640P/640x360/10FPS
		Night vision	20m
		Compression standard	H.265 /MJPEF/JPEG
		IR control	IR-CUT, Software light sensor control
		Bit rate	128 ~ 4096kbps
		Image adjustment	Vertical, horizontal adjustable, OSD support
4	Audio	Input	Built-in -32dB microphone
		Output	Built-in 8Ω2W speaker
		Sampling frequency/Bit depth	8KHz/16bit
		Compression standard/Bit rate	G711A
5	PTZ	Rotation angle	PTZ Channel: Pan 270°, Tilt 90°; Bullet channel: Pan 244°, Tilt 90°
6	4G Network	China version	FDD:B1/B3/B5/B8 TDD:B34/B38/B39/B40/B41
7	Storage	External TF card	Support TF card (up to 256GB)
		Cloud storage	Cloud storage supported (subscription required)
8	Alarm	Alarm detection	Motion detection, human detection, human framing, human tracking, siren alarm, and area detection
9	Physical Indicators	Rated Voltage	DC12V±5%
		Power Consumption	Power: 8.16W (0.68A) ; Max power: 11.4W (0.95A)
		Operating Condition	Temperature: -20 ~ 55°C; Humidity: < 90%
		Weight	Net weight: 950g Gross weight:1880g
		Product Dimension	192x286x173mm
		Package Dimension	310x190x220mm
		Carton Dimension	635x585x460mm
		QTY/CTN	12PCS
		Package Contents	1 × Camera, 1 × Screw Kit, 1 × Mounting Bracket, 1 × Power Adapter, 1 × User Manual